

SERIE 14

33YA

AVO - Wheel with avolan polyurethane and steel castor for industry,
diameter 500mm ean 16027

Material: Avolan
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, fixed. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793160278

EAN5:16027

Article code:21033A0500GCU



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 7000 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	500
Band width (mm)	100
Hub width (mm)	100
Hub version	Ball bearing
Wheel hole (mm)	50
Bearing seat (mm)	90X20
Dynamic load capacity (DaN)	7000
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	315X315
Plate hole spacing (mm)	190X190
Plate hole size (mm)	21
Offset (mm)	/
Ground clearance (mm)	630
Castor hole (mm)	/
Static load capacity (DaN)	8750
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted