

SERIE 18A

## 37ANTB

AVO - Wheel with avolan polyurethane and steel castor for industry, diameter 80mm ean 14482

**Material:** Avolan  
Polyurethane

**Core:**  
Aluminum

**Application field:**  
Industry

**Description:**

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

**Product line:** Polyurethane

**EAN13:**8018793144827 **EAN5:**14482 **Article code:**09037BA080LCU



## Features

**Minimum temperature:** -20 **Maximum temperature:** 80 **Dynamic load capacity:** 120 DaN  
**Rotation:** Ball bearing **Hardness scale:** Shore A **Hardness:** 91

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	12
Bearing seat (mm)	32X10
Dynamic load capacity (DaN)	120
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	106
Castor hole (mm)	/
Static load capacity (DaN)	150
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	20X50
Stem type	Stem(on request threaded stem) Plain axle
Finishing	Galvanized