

SERIE 19

19

AVO - Wheel with avoplus polyurethane for industry, diameter 125mm ean 14464

Material: Avoplus
Polyurethane

Core:
Aluminum

Application field:
Industry

Description:

Wheel coated with cast Soft Polyurethane tread AVOPLUS 78 Shore A with high smoothness and high thickness. Aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Product line: Polyurethane

EAN13:8018793144643

EAN5:14464

Article code:0901900125ACB



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 225 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 78

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	40
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	12
Bearing seat (mm)	32X10
Dynamic load capacity (DaN)	225
Colour	Blue
Material	Avoplus Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	78

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/