

SERIE 19V-B30

19V-B30

AVO - Wheel with avoplus polyurethane for industry, diameter 200mm ean 25208

Material: Avoplus
Polyurethane

Core:
Aluminum

Application field:
Industry

Description:

Wheel with soft AVOPLUS polyurethane 78 Shore A, round tread R30 and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Product line: Polyurethane

EAN13:8018793252089

EAN5:25208

Article code:09B1900201LCV



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 800 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 78

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	800
Colour	Green
Material	Avoplus Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	78

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/