

SERIE 19

79BIS

AVO - Wheel with avoplus polyurethane and steel castor for industry, diameter 150mm ean 14545

Material: Avoplus
Polyurethane

Core:
Aluminum

Application field:
Industry

Description:

Wheel coated with cast Soft Polyurethane tread AVOPLUS 78 Shore A with high smoothness and high thickness. Aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate and rear brake. Assembled with self-locking nut.

Product line: Polyurethane

EAN13:8018793145459

EAN5:14545

Article code:09079F0150ACB



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 300 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 78

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	50
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	300
Colour	Blue
Material	Avoplus Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	78

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	50
Ground clearance (mm)	189
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	/
Stem type	/
Finishing	Galvanized