Via XX Settembre, 107 28883 Gravellona Toce (VB) - Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 19

AVO - Wheel with avoplus polyurethane and steel castor for industry, diameter 150mm ean 14546

Application field: Material: Avoplus Core: Polyurethane Aluminum Industry

#### Description:

Wheel coated with cast Soft Polyurethane tread AVOPLUS 78 Shore A with high smoothness and high thickness. Aluminium centre. Hub on shielded ball bearings assembled with central spacer.

### **Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

Product line: Polyurethane

EAN13:8018793145466 Article code:09079BF150ACB EAN5:14546



## **Features**

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 300 DaN

Rotation: Ball bearing Hardness scale: Shore A

Hardness: 78

# **Flooring**

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

| Diameter (mm)               | 150                  |
|-----------------------------|----------------------|
| Band width (mm)             | 40                   |
| Hub width (mm)              | 50                   |
| Hub version                 | Ball bearing         |
| Wheel hole (mm)             | 20                   |
| Bearing seat (mm)           | 47X14                |
| Dynamic load capacity (DaN) | 300                  |
| Colour                      | Blue                 |
| Material                    | Avoplus Polyurethane |
| Box pieces                  | 1                    |
| Hardness scale              | Shore A              |
| Hardness                    | 78                   |

# Support data

| Plate size (mm)            | 1   |
|----------------------------|---|
| Plate hole spacing (mm)    | 1   |
| Plate hole size (mm)       | 1   |
| Offset (mm)                | 50  |
| Ground clearance (mm)      | 184                                       |
| Castor hole (mm)           | 1   |
| Static load capacity (DaN) | 380                                       |
| Structure                  | Swivel                                    |
| Version                    | Axle with brake                           |
| Brake                      | Rear                                      |
| Plain axle                 | 22X50                                     |
| Stem type                  | Plain axle Stem(on request threaded stem) |
| Finishing                  | Galvanized                                |