

SERIE 19V-B30

## 69AV-B30

**AVO - Wheel with avoplus polyurethane and steel castor for industry, diameter 160mm ean 24848**

**Material:** Avoplus  
Polyurethane

**Core:**  
Aluminum

**Application field:**  
Industry

**Description:**

Wheel with soft AVOPLUS polyurethane 78 Shore A, round tread R30 and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut.

**Product line:** Polyurethane

**EAN13:**8018793248488

**EAN5:**24848

**Article code:**09369A016BACV



### Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 300 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 78

### Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

### Wheel data

|                             |                      |
|-----------------------------|----------------------|
| Diameter (mm)               | 160                  |
| Band width (mm)             | 50                   |
| Hub width (mm)              | 60                   |
| Hub version                 | Ball bearing         |
| Wheel hole (mm)             | 20                   |
| Bearing seat (mm)           | 47X14                |
| Dynamic load capacity (DaN) | 300                  |
| Colour                      | Green                |
| Material                    | Avoplus Polyurethane |
| Box pieces                  | /                    |
| Hardness scale              | Shore A              |
| Hardness                    | 78                   |

### Support data

|                            |            |
|----------------------------|------------|
| Plate size (mm)            | 140X110    |
| Plate hole spacing (mm)    | 105X080    |
| Plate hole size (mm)       | 11X16      |
| Offset (mm)                | /          |
| Ground clearance (mm)      | 197        |
| Castor hole (mm)           | /          |
| Static load capacity (DaN) | 380        |
| Structure                  | Fixed      |
| Version                    | /          |
| Brake                      | /          |
| Plain axle                 | /          |
| Stem type                  | /          |
| Finishing                  | Galvanized |