

SERIE 19V-B30

## 79AV-B30

AVO - Wheels with polyurethane avoplus with castor steel for industry, diameter 160mm ean 26026

**Material:** / **Core:** Aluminum **Scope:** Industry

**Description:**

Wheel with soft AVOPLUS polyurethane round tread 78 Shore A. Aluminium centre. Hub on shielded ball bearings assembled with central spacer. R30

**Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut.

**Product line:** Polyurethane

**EAN13:**8018793260268 **EAN5:**26026 **Article code:**9079A0160BACV



### Features

**Minimum temperature:** -20 **Maximum temperature:** 80 **Dynamic load capacity:** 400 DaN  
**Rotation:** Ball bearing **Hardness scale:** Shore A **Hardness:** 78

### Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

### Wheel data

|                             |              |
|-----------------------------|--------------|
| Diameter (mm)               | 160          |
| Band width (mm)             | 50           |
| Hub width (mm)              | 60           |
| Hub version                 | Ball bearing |
| Wheel hole (mm)             | 20           |
| Bearing seat (mm)           | 47X14        |
| Dynamic load capacity (DaN) | 400          |
| Colour                      | Green        |
| Material                    | /            |
| Box pieces                  | /            |
| Hardness scale              | Shore A      |
| Hardness                    | 78           |

### Support data

|                            |            |
|----------------------------|------------|
| Plate size (mm)            | /          |
| Plate hole spacing (mm)    | /          |
| Plate hole size (mm)       | /          |
| Offset (mm)                | /          |
| Ground clearance (mm)      | 216        |
| Castor hole (mm)           | /          |
| Static load capacity (DaN) | 500        |
| Structure                  | Fixed      |
| Version                    | /          |
| Brake                      | /          |
| Plain axle                 | /          |
| Stem type                  | /          |
| Finishing                  | Galvanized |