

SERIE 19V-B30

79BISBV-B30

AVO - Wheels with polyurethane avoplus with castor steel for industry, diameter 160mm ean 26047

Material: / **Core:** Aluminum **Scope:** Industry

Description:

Wheel with soft AVOPLUS polyurethane round tread 78 Shore A. Aluminium centre. Hub on shielded ball bearings assembled with central spacer. R30

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

Product line: Polyurethane

EAN13:8018793260473 **EAN5:**26047 **Article code:**9079BF160BACV



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 400 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 78

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	160
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	400
Colour	Green
Material	/
Box pieces	/
Hardness scale	Shore A
Hardness	78

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	57
Ground clearance (mm)	209
Castor hole (mm)	/
Static load capacity (DaN)	500
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	25X65
Stem type	Stem(on request threaded stem)
Finishing	Galvanized