

SERIE 19V-B30

## 79BISBV-B30

AVO - Wheel with avoplus polyurethane and steel castor for industry, diameter 180mm ean 26941

**Material:** Avoplus  
Polyurethane

**Core:**  
Aluminum

**Application field:**  
Industry

**Description:**

Wheel with soft AVOPLUS polyurethane 78 Shore A, round tread R30 and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

**Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

**Product line:** Polyurethane

**EAN13:**8018793269414    **EAN5:**26941    **Article code:**09079BF18BACV



### Features

**Minimum temperature:** -20    **Maximum temperature:** 80    **Dynamic load capacity:** 500 DaN  
**Rotation:** Ball bearing    **Hardness scale:** Shore A    **Hardness:** 78

### Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

### Wheel data

Diameter (mm)	180
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	500
Colour	Green
Material	Avoplus Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	78

### Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	57
Ground clearance (mm)	234
Castor hole (mm)	/
Static load capacity (DaN)	630
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	25X65
Stem type	Stem(on request threaded stem) Plain axle
Finishing	Galvanized