

SERIE 19V-B30

79BISV-B30

AVO - Wheel with avoplus polyurethane and steel castor for industry, diameter 180mm ean 26942

Material: Avoplus
Polyurethane

Core:
Aluminum

Application field:
Industry

Description:

Wheel with soft AVOPLUS polyurethane 78 Shore A, round tread R30 and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate and rear brake. Assembled with self-locking nut.

Product line: Polyurethane

EAN13:8018793269421

EAN5:26942

Article code:09079F018BACV



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 500 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 78

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	180
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	500
Colour	Green
Material	Avoplus Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	78

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	57
Ground clearance (mm)	241
Castor hole (mm)	/
Static load capacity (DaN)	630
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	/
Stem type	/
Finishing	Galvanized