

SERIE 19

79B

AVO - Wheel with avoplus polyurethane and steel castor for industry, diameter 200mm ean 14559

Material: Avoplus Polyurethane **Core:** Aluminum **Scope:** Industry

Description:

Wheel coated with cast Soft Polyurethane tread AVOPLUS 78 Shore A with high smoothness and high thickness. Aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem. Assembled with self-locking nut.

Product line: Polyurethane

EAN13:8018793145596 **EAN5:**14559 **Article code:**09079B0200ACB



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 700 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 78

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	700
Colour	Blue
Material	Avoplus Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	78

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	57
Ground clearance (mm)	244
Castor hole (mm)	/
Static load capacity (DaN)	880
Structure	Swivel
Version	Axle
Brake	/
Plain axle	25X65
Stem type	Stem(on request threaded stem) Plain axle
Finishing	Galvanized