

SERIE 19

## 79BISB

**AVO - Wheel with avoplus polyurethane and steel castor for industry, diameter 200mm ean 14561**

**Material:** Avoplus Polyurethane    **Core:** Aluminum    **Scope:** Industry

**Description:**

Wheel coated with cast Soft Polyurethane tread AVOPLUS 78 Shore A with high smoothness and high thickness. Aluminium centre. Hub on shielded ball bearings assembled with central spacer.

**Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

**Product line:** Polyurethane

**EAN13:**8018793145619    **EAN5:**14561    **Article code:**09079BF200ACB



## Features

**Minimum temperature:** -20    **Maximum temperature:** 80    **Dynamic load capacity:** 700 DaN  
**Rotation:** Ball bearing    **Hardness scale:** Shore A    **Hardness:** 78

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	700
Colour	Blue
Material	Avoplus Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	78

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	57
Ground clearance (mm)	244
Castor hole (mm)	/
Static load capacity (DaN)	880
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	25X65
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized