

SERIE 19V-B30

69BV-B30

AVO - Wheels with polyurethane avoplus with castor steel for industry, diameter 250mm ean 25993

Material: / **Core:** Aluminum **Scope:** Industry

Description:

Wheel with soft AVOPLUS polyurethane round tread 78 Shore A. Aluminium centre. Hub on shielded ball bearings assembled with central spacer. R30

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem. Assembled with self-locking nut.

Product line: Polyurethane

EAN13:8018793259934 **EAN5:**25993 **Article code:**9069B0250BACV



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 300 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 78

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	250
Band width (mm)	50
Hub width (mm)	20
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	300
Colour	Green
Material	/
Box pieces	/
Hardness scale	Shore A
Hardness	78

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	85
Ground clearance (mm)	302
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Axle
Brake	/
Plain axle	25X55
Stem type	Stem(on request threaded stem)
Finishing	Galvanized