

SERIE 19V-B30

79BISV-B30

AVO - Wheels with polyurethane avoplus with castor steel for industry, diameter 250mm ean 26043

Material: / **Core:** Aluminum **Scope:** Industry

Description:

Wheel with soft AVOPLUS polyurethane round tread 78 Shore A. Aluminium centre. Hub on shielded ball bearings assembled with central spacer. R30

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate and rear brake. Assembled with self-locking nut.

Product line: Polyurethane

EAN13:8018793260435 **EAN5:**26043 **Article code:**9079F0250BACV



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 800 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 78

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	250
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	800
Colour	Green
Material	/
Box pieces	/
Hardness scale	Shore A
Hardness	78

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	74
Ground clearance (mm)	300
Castor hole (mm)	/
Static load capacity (DaN)	1000
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	/
Stem type	/
Finishing	Galvanized