

SERIE 19V-B30

## 79V-B30

AVO - Wheel with avoplus polyurethane and steel castor for industry, diameter 80mm ean 26949

**Material:** Avoplus  
Polyurethane

**Core:**  
Aluminum

**Application field:**  
Industry

**Description:**

Wheel with soft AVOPLUS polyurethane 78 Shore A, round tread R30 and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

**Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate. Assembled with self-locking nut.

**Product line:** Polyurethane

**EAN13:**8018793269490

**EAN5:**26949

**Article code:**090790081BACV



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 150 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 78

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

|                             |                      |
|-----------------------------|----------------------|
| Diameter (mm)               | 80                   |
| Band width (mm)             | 25                   |
| Hub width (mm)              | 30                   |
| Hub version                 | Ball bearing         |
| Wheel hole (mm)             | 12                   |
| Bearing seat (mm)           | 32X10                |
| Dynamic load capacity (DaN) | 150                  |
| Colour                      | Green                |
| Material                    | Avoplus Polyurethane |
| Box pieces                  | /                    |
| Hardness scale              | Shore A              |
| Hardness                    | 78                   |

## Support data

|                            |            |
|----------------------------|------------|
| Plate size (mm)            | 100X085    |
| Plate hole spacing (mm)    | 080X060    |
| Plate hole size (mm)       | 9X12       |
| Offset (mm)                | 36         |
| Ground clearance (mm)      | 118        |
| Castor hole (mm)           | /          |
| Static load capacity (DaN) | 190        |
| Structure                  | Swivel     |
| Version                    | Plate      |
| Brake                      | /          |
| Plain axle                 | /          |
| Stem type                  | /          |
| Finishing                  | Galvanized |