

SERIE 19V-B30

## 69BV-B30

**AVO - Wheel with avoplus polyurethane and steel castor for industry, diameter 80mm ean 27653**

**Material:** Avoplus  
Polyurethane

**Core:**  
Aluminum

**Application field:**  
Industry

**Description:**

Wheel with soft AVOPLUS polyurethane 78 Shore A, round tread R30 and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem. Assembled with self-locking nut.

**Product line:** Polyurethane

**EAN13:**8018793276535

**EAN5:**27653

**Article code:**09369B008BACV



### Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 120 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 78

### Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

### Wheel data

|                             |                      |
|-----------------------------|----------------------|
| Diameter (mm)               | 80                   |
| Band width (mm)             | 25                   |
| Hub width (mm)              | 30                   |
| Hub version                 | Ball bearing         |
| Wheel hole (mm)             | 12                   |
| Bearing seat (mm)           | 32X10                |
| Dynamic load capacity (DaN) | 120                  |
| Colour                      | Green                |
| Material                    | Avoplus Polyurethane |
| Box pieces                  | /                    |
| Hardness scale              | Shore A              |
| Hardness                    | 78                   |

### Support data

|                            |                                           |
|----------------------------|-------------------------------------------|
| Plate size (mm)            | /                                         |
| Plate hole spacing (mm)    | /                                         |
| Plate hole size (mm)       | /                                         |
| Offset (mm)                | 37                                        |
| Ground clearance (mm)      | 108                                       |
| Castor hole (mm)           | /                                         |
| Static load capacity (DaN) | 150                                       |
| Structure                  | Swivel                                    |
| Version                    | Axle                                      |
| Brake                      | /                                         |
| Plain axle                 | 20X50                                     |
| Stem type                  | Plain axle Stem(on request threaded stem) |
| Finishing                  | Galvanized                                |