

SERIE 601

601

AVO - Wheel with avoprene polyurethane for industry, diameter 250mm ean 15143

Material: Avoprene Polyurethane

Core: Electro-welded steel

Application field: Industry

Description:

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A and electro-welded steel centre. Hub on shielded and sealed ball bearings.

Product line: Polyurethane

EAN13:8018793151436

EAN5:15143

Article code:0806012250XCA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 4000 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	250
Band width (mm)	150
Hub width (mm)	150
Hub version	Ball bearing
Wheel hole (mm)	50
Bearing seat (mm)	90X23
Dynamic load capacity (DaN)	4000
Colour	Brown
Material	Avoprene Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/