

SERIE 15

15

AVO - Wheel with avoprene polyurethane for industry, diameter 400mm ean 15440

Material: Avoprene
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Product line: Polyurethane

EAN13:8018793154406

EAN5:15440

Article code:0801500400XCA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 4600 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	400
Band width (mm)	125
Hub width (mm)	125
Hub version	Ball bearing
Wheel hole (mm)	40
Bearing seat (mm)	80X18
Dynamic load capacity (DaN)	4600
Colour	Brown
Material	Avoprene Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/