

SERIE 15

30A

AVO - Wheel with avoprene polyurethane and steel castor for industry, diameter 100mm ean 06582

Material: Avoprene
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Extra Heavy-Duty Castors:

Made of in pressed and welded high thickness steel, fixed. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793065825 **EAN5:**06582 **Article code:**13030A0100SCA



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 200 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	25
Hub width (mm)	25
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	200
Colour	Brown
Material	Avoprene Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	11
Offset (mm)	/
Ground clearance (mm)	150
Castor hole (mm)	/
Static load capacity (DaN)	250
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted