

SERIE 15

## 23ANT

**AVO - Wheel with avoprene polyurethane and steel castor for industry, diameter 100mm ean 10573**

**Material:** Avoprene  
Polyurethane

**Core:** Cast  
Iron

**Application field:**  
Industry

**Description:**

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Polyurethane

**EAN13:**8018793105736

**EAN5:**10573

**Article code:**080230F100LCA



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 120 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 91

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

|                             |                       |
|-----------------------------|-----------------------|
| Diameter (mm)               | 100                   |
| Band width (mm)             | 30                    |
| Hub width (mm)              | 30                    |
| Hub version                 | Ball bearing          |
| Wheel hole (mm)             | 15                    |
| Bearing seat (mm)           | 35X11                 |
| Dynamic load capacity (DaN) | 120                   |
| Colour                      | Brown                 |
| Material                    | Avoprene Polyurethane |
| Box pieces                  | /                     |
| Hardness scale              | Shore A               |
| Hardness                    | 91                    |

## Support data

|                            |                  |
|----------------------------|------------------|
| Plate size (mm)            | 100X085          |
| Plate hole spacing (mm)    | 080X060          |
| Plate hole size (mm)       | 8,5X12           |
| Offset (mm)                | 37               |
| Ground clearance (mm)      | 128              |
| Castor hole (mm)           | /                |
| Static load capacity (DaN) | 150              |
| Structure                  | Swivel           |
| Version                    | Plate with brake |
| Brake                      | Front            |
| Plain axle                 | /                |
| Stem type                  | /                |
| Finishing                  | Galvanized       |