

SERIE 18M-B

## 75BISB-B

AVO - Wheel with avoprene polyurethane and steel castor for industry, diameter 100mm ean 24381

**Material:** Avoprene  
Polyurethane

**Core:**  
Aluminum

**Application field:**  
Industry

**Description:**

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A, rounded tread and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

**Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

**Product line:** Polyurethane

**EAN13:**8018793243810    **EAN5:**24381    **Article code:**11075FS10BABM



## Features

|                                 |                                |                                       |
|---------------------------------|--------------------------------|---------------------------------------|
| <b>Minimum temperature:</b> -20 | <b>Maximum temperature:</b> 80 | <b>Dynamic load capacity:</b> 200 DaN |
| <b>Rotation:</b> Ball bearing   | <b>Hardness scale:</b> Shore A | <b>Hardness:</b> 91                   |

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

|                                    |                       |
|------------------------------------|-----------------------|
| <b>Diameter (mm)</b>               | 100                   |
| <b>Band width (mm)</b>             | 30                    |
| <b>Hub width (mm)</b>              | 40                    |
| <b>Hub version</b>                 | Ball bearing          |
| <b>Wheel hole (mm)</b>             | 12                    |
| <b>Bearing seat (mm)</b>           | 32X10                 |
| <b>Dynamic load capacity (DaN)</b> | 200                   |
| <b>Colour</b>                      | Brown                 |
| <b>Material</b>                    | Avoprene Polyurethane |
| <b>Box pieces</b>                  | /                     |
| <b>Hardness scale</b>              | Shore A               |
| <b>Hardness</b>                    | 91                    |

## Support data

|                                   |                                              |
|-----------------------------------|----------------------------------------------|
| <b>Plate size (mm)</b>            | /                                            |
| <b>Plate hole spacing (mm)</b>    | /                                            |
| <b>Plate hole size (mm)</b>       | /                                            |
| <b>Offset (mm)</b>                | 36                                           |
| <b>Ground clearance (mm)</b>      | 131                                          |
| <b>Castor hole (mm)</b>           | /                                            |
| <b>Static load capacity (DaN)</b> | 250                                          |
| <b>Structure</b>                  | Swivel                                       |
| <b>Version</b>                    | Axle with brake                              |
| <b>Brake</b>                      | Rear                                         |
| <b>Plain axle</b>                 | 12X20                                        |
| <b>Stem type</b>                  | Threaded axle Stem(on request threaded stem) |
| <b>Finishing</b>                  | Galvanized                                   |