

SERIE 15

## 28B

**AVO - Wheel made of avoprene polyurethane with steel castor for industry, diameter 125mm ean 10613**

**Material:** Avoprene Polyurethane    **Core:** Cast Iron    **Scope:** Industry

**Description:**

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

**Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

**Product line:** Polyurethane

**EAN13:**8018793106139    **EAN5:**10613    **Article code:**10028B0125XCA



## Features

**Minimum temperature:** -20    **Maximum temperature:** 80    **Dynamic load capacity:** 400 DaN  
**Rotation:** Ball bearing    **Hardness scale:** Shore A    **Hardness:** 91

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

|                             |                       |
|-----------------------------|-----------------------|
| Diameter (mm)               | 125                   |
| Band width (mm)             | 40                    |
| Hub width (mm)              | 40                    |
| Hub version                 | Ball bearing          |
| Wheel hole (mm)             | 20                    |
| Bearing seat (mm)           | 47X14                 |
| Dynamic load capacity (DaN) | 400                   |
| Colour                      | Brown                 |
| Material                    | Avoprene Polyurethane |
| Box pieces                  | /                     |
| Hardness scale              | Shore A               |
| Hardness                    | 91                    |

## Support data

|                            |                                |
|----------------------------|--------------------------------|
| Plate size (mm)            | /                              |
| Plate hole spacing (mm)    | /                              |
| Plate hole size (mm)       | /                              |
| Offset (mm)                | 45                             |
| Ground clearance (mm)      | 161                            |
| Castor hole (mm)           | /                              |
| Static load capacity (DaN) | 500                            |
| Structure                  | Swivel                         |
| Version                    | Axle with brake                |
| Brake                      | Rear                           |
| Plain axle                 | 22X50                          |
| Stem type                  | Stem(on request threaded stem) |
| Finishing                  | Galvanized                     |