

SERIE 15

## 20B

**AVO - Wheel with avoprene polyurethane and steel castor for industry, diameter 125mm ean 14010**

**Material:** Avoprene  
Polyurethane

**Core:** Cast  
Iron

**Application field:**  
Industry

**Description:**

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem. Assembled with self-locking nut.

**Product line:** Polyurethane

**EAN13:**8018793140102    **EAN5:**14010    **Article code:**08020B0125YCA



## Features

**Minimum temperature:** -20    **Maximum temperature:** 80    **Dynamic load capacity:** 170 DaN  
**Rotation:** Ball bearing    **Hardness scale:** Shore A    **Hardness:** 91

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

|                                    |                       |
|------------------------------------|-----------------------|
| <b>Diameter (mm)</b>               | 125                   |
| <b>Band width (mm)</b>             | 35                    |
| <b>Hub width (mm)</b>              | 35                    |
| <b>Hub version</b>                 | Ball bearing          |
| <b>Wheel hole (mm)</b>             | 20                    |
| <b>Bearing seat (mm)</b>           | 47X14                 |
| <b>Dynamic load capacity (DaN)</b> | 170                   |
| <b>Colour</b>                      | Brown                 |
| <b>Material</b>                    | Avoprene Polyurethane |
| <b>Box pieces</b>                  | /                     |
| <b>Hardness scale</b>              | Shore A               |
| <b>Hardness</b>                    | 91                    |

## Support data

|                                   |   |
|-----------------------------------|---|
| <b>Plate size (mm)</b>            | /   |
| <b>Plate hole spacing (mm)</b>    | /   |
| <b>Plate hole size (mm)</b>       | /   |
| <b>Offset (mm)</b>                | 42  |
| <b>Ground clearance (mm)</b>      | 150                                       |
| <b>Castor hole (mm)</b>           | /   |
| <b>Static load capacity (DaN)</b> | 220                                       |
| <b>Structure</b>                  | Swivel                                    |
| <b>Version</b>                    | Axle                                      |
| <b>Brake</b>                      | /   |
| <b>Plain axle</b>                 | 22X50                                     |
| <b>Stem type</b>                  | Plain axle Stem(on request threaded stem) |
| <b>Finishing</b>                  | Galvanized                                |