

SERIE 15

# 33A

AVO - Wheel with avoprene polyurethane and steel castor for industry, diameter 125mm ean 16034

**Material:** Avoprene  
Polyurethane

**Core:** Cast  
Iron

**Application field:**  
Industry

**Description:**

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

**Twin Wheel Extra Heavy-Duty Castors:**

Made of pressed and welded high thickness steel, fixed. Black epoxy paint.

**Product line:** Polyurethane

**EAN13:**8018793160346

**EAN5:**16034

**Article code:**13033A0125LCA



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 600 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 91

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

|                             |                       |
|-----------------------------|-----------------------|
| Diameter (mm)               | 125                   |
| Band width (mm)             | 30                    |
| Hub width (mm)              | 30                    |
| Hub version                 | Ball bearing          |
| Wheel hole (mm)             | 15                    |
| Bearing seat (mm)           | 35X11                 |
| Dynamic load capacity (DaN) | 600                   |
| Colour                      | Brown                 |
| Material                    | Avoprene Polyurethane |
| Box pieces                  | /                     |
| Hardness scale              | Shore A               |
| Hardness                    | 91                    |

## Support data

|                            |               |
|----------------------------|---------------|
| Plate size (mm)            | 170X170       |
| Plate hole spacing (mm)    | 130X130       |
| Plate hole size (mm)       | 13            |
| Offset (mm)                | /             |
| Ground clearance (mm)      | 197           |
| Castor hole (mm)           | /             |
| Static load capacity (DaN) | 750           |
| Structure                  | Fixed         |
| Version                    | /             |
| Brake                      | /             |
| Plain axle                 | /             |
| Stem type                  | /             |
| Finishing                  | Black painted |