

SERIE 15

20

AVO - Wheel with avoprene polyurethane and steel castor for industry, diameter 125mm ean 20067

Material: Avoprene
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Polyurethane

EAN13:8018793200677

EAN5:20067

Article code:0802000126SCA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 170 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	25
Hub width (mm)	25
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	170
Colour	Brown
Material	Avoprene Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	42
Ground clearance (mm)	155
Castor hole (mm)	/
Static load capacity (DaN)	220
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized