

SERIE 15

30A

AVO - Wheel with avoprene polyurethane and steel castor for industry, diameter 150mm ean 06595

Material: Avoprene
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Extra Heavy-Duty Castors:

Made of in pressed and welded high thickness steel, fixed. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793065955

EAN5:06595

Article code:13030A0150YCA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 650 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	50
Hub width (mm)	50
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	650
Colour	Brown
Material	Avoprene Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13
Offset (mm)	/
Ground clearance (mm)	205
Castor hole (mm)	/
Static load capacity (DaN)	820
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted