

SERIE 15

33

AVO - Wheel with avoprene polyurethane and steel castor for industry, diameter 150mm ean 06711

Material: Avoprene
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793067119

EAN5:06711

Article code:1303300150LCA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 900 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	35
Hub width (mm)	35
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	900
Colour	Brown
Material	Avoprene Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	170X170
Plate hole spacing (mm)	130X130
Plate hole size (mm)	13
Offset (mm)	60
Ground clearance (mm)	210
Castor hole (mm)	/
Static load capacity (DaN)	1130
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted