

SERIE 15

30BISB

AVO - Wheel made of avoprene polyurethane with steel castor for industry, diameter 150mm ean 10761

Material: Avoprene Polyurethane **Core:** Cast Iron **Scope:** Industry

Description:

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem and rear brake. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793107617 **EAN5:**10761 **Article code:**13030BF150LCA



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 450 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	35
Hub width (mm)	35
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	450
Colour	Brown
Material	Avoprene Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	50
Ground clearance (mm)	205
Castor hole (mm)	/
Static load capacity (DaN)	570
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	22X50
Stem type	Stem(on request threaded stem)
Finishing	Black painted