Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

#### SERIE 15

28**B** 

AVO - Wheel with avoprene polyurethane and steel castor for industry, diameter 175mm ean 10617

Material: AvopreneCore: CastApplication field:PolyurethaneIronIndustry

Description:

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

### **Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

Product line: Polyurethane

**EAN13**:8018793106177 **EAN5**:10617 **Article code**:10028B0175LCA



## **Features**

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 650 DaN

Rotation: Ball bearing Hardness scale: Shore A Hardness: 91

# **Flooring**

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

Diameter (mm)	175
Band width (mm)	40
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	650
Colour	Brown
Material	Avoprene Polyurethane
Box pieces	1
Hardness scale	Shore A
Hardness	91

## Support data

Plate size (mm)	I
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	57
Ground clearance (mm)	231
Castor hole (mm)	1
Static load capacity (DaN)	820
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	25X65
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized