

SERIE 15

30BISB

AVO - Wheel with avoprene polyurethane and steel castor for industry, diameter 175mm ean 10764

Material: Avoprene Polyurethane **Core:** Cast Iron **Scope:** Industry

Description:

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem and rear brake. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793107648 **EAN5:**10764 **Article code:**13030BF175LCA



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 650 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

| | |
|-----------------------------|-----------------------|
| Diameter (mm) | 175 |
| Band width (mm) | 40 |
| Hub width (mm) | 40 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 20 |
| Bearing seat (mm) | 47X14 |
| Dynamic load capacity (DaN) | 650 |
| Colour | Brown |
| Material | Avoprene Polyurethane |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 91 |

Support data

| | |
|----------------------------|---|
| Plate size (mm) | / |
| Plate hole spacing (mm) | / |
| Plate hole size (mm) | / |
| Offset (mm) | 57 |
| Ground clearance (mm) | 248 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 820 |
| Structure | Swivel |
| Version | Axle with brake |
| Brake | Rear |
| Plain axle | 25X65 |
| Stem type | Plain axle Stem(on request threaded stem) |
| Finishing | Black painted |