Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 15

# 30BISB

AVO - Wheel with avoprene polyurethane and steel castor for industry, diameter 200mm ean 06611

**Material:** Avoprene Polyurethane

Core: Cast Iron Application field: Industry

### Description:

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

#### **Extra Heavy-Duty Castors:**

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem and rear brake. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793066112 EAN5

EAN5:06611

Article code:13030BF200LCA



# **Flooring**

Asphalt

• Concrete

Grid

Minimum temperature: -20

Rotation: Ball bearing

**Features** 

Maximum temperature: 80

Hardness scale: Shore A Hardness: 91

Stoneware

### Wheel data

Diameter (mm)	200
Band width (mm)	45
Hub width (mm)	45
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	1000
Colour	Brown
Material	Avoprene Polyurethane
Box pieces	1
Hardness scale	Shore A
Hardness	91

## Support data

Dynamic load capacity: 1000 DaN

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	57
Ground clearance (mm)	260
Castor hole (mm)	1
Static load capacity (DaN)	1250
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	25X65
Stem type	Stem(on request threaded stem) Plain axle
Finishing	Black painted