

SERIE 15

23ANTB

AVO - Wheel with avoprene polyurethane and steel castor for industry, diameter 200mm ean 10559

Material: Avoprene
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

Product line: Polyurethane

EAN13:8018793105590

EAN5:10559

Article code:08023BF200LCA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 300 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

| | |
|------------------------------------|-----------------------|
| Diameter (mm) | 200 |
| Band width (mm) | 45 |
| Hub width (mm) | 45 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 25 |
| Bearing seat (mm) | 52X15 |
| Dynamic load capacity (DaN) | 300 |
| Colour | Brown |
| Material | Avoprene Polyurethane |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 91 |

Support data

| | |
|-----------------------------------|--|
| Plate size (mm) | / |
| Plate hole spacing (mm) | / |
| Plate hole size (mm) | / |
| Offset (mm) | 55 |
| Ground clearance (mm) | 232 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 380 |
| Structure | Swivel |
| Version | Axle with brake |
| Brake | Front |
| Plain axle | 22X50 |
| Stem type | Stem(on request threaded stem) Plain axle |
| Finishing | Galvanized |