

SERIE 15

30B

AVO - Wheel with avoprene polyurethane and steel castor for industry, diameter 200mm ean 10771

Material: Avoprene
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793107716

EAN5:10771

Article code:13030B0200XCA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 1100 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	1100
Colour	Brown
Material	Avoprene Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	57
Ground clearance (mm)	260
Castor hole (mm)	/
Static load capacity (DaN)	1380
Structure	Swivel
Version	Axle
Brake	/
Plain axle	25X65
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Black painted