

SERIE 15

33DIR

AVO - Wheel with avoprene polyurethane and steel castor for industry, diameter 200mm ean 24826

Material: Avoprene
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate and directional lock. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793248266

EAN5:24826

Article code:13033DI200XCA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 2000 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	2000
Colour	Brown
Material	Avoprene Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	200X200
Plate hole spacing (mm)	160X160
Plate hole size (mm)	17
Offset (mm)	72
Ground clearance (mm)	270
Castor hole (mm)	/
Static load capacity (DaN)	2500
Structure	Swivel
Version	Plate with brake
Brake	Directional lock
Plain axle	/
Stem type	/
Finishing	Black painted