Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 15

30B

AVO - Wheel with avoprene polyurethane and steel castor for industry, diameter 250mm ean 06648

Material: Avoprene Polyurethane

Core: Cast Iron Application field: Industry

Description:

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793066488

EAN5:06648

Article code:13030B0250LCA



Features Flooring

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 1400 DaN

Rotation: Ball bearing Hardness scale: Shore A

Hardness: 91

Asphalt

ConcreteGrid

Stoneware

Wheel data

Diameter (mm)	250
Band width (mm)	60
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	1400
Colour	Brown
Material	Avoprene Polyurethane
Box pieces	1
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	80
Ground clearance (mm)	305
Castor hole (mm)	1
Static load capacity (DaN)	1750
Structure	Swivel
Version	Axle
Brake	1
Plain axle	40X80
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Black painted