

SERIE 15

30BIS

AVO - Wheel with avoprene polyurethane and steel castor for industry, diameter 250mm ean 17770

Material: Avoprene
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate and rear brake. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793177702

EAN5:17770

Article code:130300F250LCA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 1400 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	250
Band width (mm)	60
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	1400
Colour	Brown
Material	Avoprene Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	175X140
Plate hole spacing (mm)	140X105
Plate hole size (mm)	15
Offset (mm)	80
Ground clearance (mm)	305
Castor hole (mm)	/
Static load capacity (DaN)	1750
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	/
Stem type	/
Finishing	Black painted