

SERIE 15

30B

AVO - Wheel with avoprene polyurethane and steel castor for industry, diameter 300mm ean 06650

Material: Avoprene
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793066501

EAN5:06650

Article code:13030B0300LCA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 1800 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	300
Band width (mm)	70
Hub width (mm)	70
Hub version	Ball bearing
Wheel hole (mm)	30
Bearing seat (mm)	62X16
Dynamic load capacity (DaN)	1800
Colour	Brown
Material	Avoprene Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	83
Ground clearance (mm)	370
Castor hole (mm)	/
Static load capacity (DaN)	2250
Structure	Swivel
Version	Axle
Brake	/
Plain axle	50X90
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Black painted