

SERIE 15

33

AVO - Wheel with avoprene polyurethane and steel castor for industry, diameter 400mm ean 16038

Material: Avoprene
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793160384

EAN5:16038

Article code:1303300400GCA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 6000 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	400
Band width (mm)	100
Hub width (mm)	100
Hub version	Ball bearing
Wheel hole (mm)	40
Bearing seat (mm)	80X18
Dynamic load capacity (DaN)	6000
Colour	Brown
Material	Avoprene Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	315X315
Plate hole spacing (mm)	250X250
Plate hole size (mm)	21
Offset (mm)	100
Ground clearance (mm)	530
Castor hole (mm)	/
Static load capacity (DaN)	7500
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted