Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 15

# **23ANTB**

AVO - Wheel with avoprene polyurethane and steel castor for industry, diameter 60mm ean 21258

**Material:** Avoprene Polyurethane

Core: Cast Iron Application field: Industry

#### Description:

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

#### Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

Product line: Polyurethane

EAN13:8018793212588

EAN5:21258

Article code:08023BF060LCA



### **Features**

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 120 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

# **Flooring**

- Asphalt
- Concrete
- Grid
- Stoneware

#### Wheel data

| Diameter (mm)               | 60                    |
|-----------------------------|-----------------------|
| Band width (mm)             | 30                    |
| Hub width (mm)              | 30                    |
| Hub version                 | Ball bearing          |
| Wheel hole (mm)             | 15                    |
| Bearing seat (mm)           | 35X11                 |
| Dynamic load capacity (DaN) | 120                   |
| Colour                      | Brown                 |
| Material                    | Avoprene Polyurethane |
| Box pieces                  | 1                     |
| Hardness scale              | Shore A               |
| Hardness                    | 91                    |

## Support data

| Plate size (mm)            | 1   |
|----------------------------|---|
| Plate hole spacing (mm)    | 1   |
| Plate hole size (mm)       | 1   |
| Offset (mm)                | 37  |
| Ground clearance (mm)      | 87  |
| Castor hole (mm)           | 1   |
| Static load capacity (DaN) | 150                                       |
| Structure                  | Swivel                                    |
| Version                    | Axle with brake                           |
| Brake                      | Front                                     |
| Plain axle                 | 20X50                                     |
| Stem type                  | Plain axle Stem(on request threaded stem) |
| Finishing                  | Galvanized                                |