

SERIE 18M-B

74ANTF-B

AVO - Wheel with avoprene polyurethane and steel castor for industry, diameter 80mm ean 23611

Material: Avoprene
Polyurethane

Core:
Aluminum

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A, rounded tread and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole and front brake. Assembled with self-locking nut.

Product line: Polyurethane

EAN13:8018793236119

EAN5:23611

Article code:09074FA080ABM



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 120 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	80
Band width (mm)	25
Hub width (mm)	30
Hub version	Ball bearing
Wheel hole (mm)	12
Bearing seat (mm)	32X10
Dynamic load capacity (DaN)	120
Colour	Brown
Material	Avoprene Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	106
Castor hole (mm)	12
Static load capacity (DaN)	150
Structure	Swivel
Version	Bolt hole with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	Galvanized