

SERIE 15

28B

AVO - Wheel with avoprene polyurethane and steel castor for industry, diameter 80mm ean 26978

Material: Avoprene
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

Product line: Polyurethane

EAN13:8018793269780

EAN5:26978

Article code:10028B28036CA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 250 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	80
Band width (mm)	36
Hub width (mm)	36
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	250
Colour	Brown
Material	Avoprene Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	36
Ground clearance (mm)	114
Castor hole (mm)	/
Static load capacity (DaN)	320
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	16X50
Stem type	Threaded axle
Finishing	Galvanized