

SERIE 18AH

18AH

AVO - Wheel with avotop polyurethane for industry, diameter 100mm ean 23583

Material: Avotop
Polyurethane

Core:
Aluminum

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOTOP 95 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer. Ideal for all environments and for the most demanding conditions of use such as speed, heavy duties and frequent use. The 18AH wheel can be assembled with all medium and heavy-duty castors.

Product line: Polyurethane

EAN13:8018793235839

EAN5:23583

Article code:09018A1100LCH



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 250 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 95

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	40
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	12
Bearing seat (mm)	32X10
Dynamic load capacity (DaN)	250
Colour	Purple
Material	Avotop Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	95

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/