

SERIE 14H

14H

AVO - Wheel with avotop polyurethane for industry, diameter 150mm ean 18926

Material: Avotop
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOTOP 95 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer. Ideal for all environments and for the most demanding conditions of use such as speed, heavy duties and frequent use. The 14H wheel can be assembled with all medium, heavy and extra heavy-duty castors including twin wheel versions.

Product line: Polyurethane

EAN13: 8018793189262

EAN5: 18926

Article code: 0901400150XCH



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 500 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 95

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	500
Colour	Purple
Material	Avotop Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	95

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/