

SERIE 14H

14H

AVO - Wheel with avotop polyurethane for industry, diameter 150mm ean 21784

Material: Avotop
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOTOP 95 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer. Ideal for all environments and for the most demanding conditions of use such as speed, heavy duties and frequent use. The 14H wheel can be assembled with all medium, heavy and extra heavy-duty castors including twin wheel versions.

Product line: Polyurethane

EAN13: 8018793217842

EAN5: 21784

Article code: 0901400150SCH



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 400 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 95

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	30
Hub width (mm)	30
Hub version	Ball bearing
Wheel hole (mm)	17
Bearing seat (mm)	40X12
Dynamic load capacity (DaN)	400
Colour	Purple
Material	Avotop Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	95

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/