

SERIE 14W

14W

AVO - Wheel with avowater polyurethane for industry, diameter 250mm ean 25551

Material: Avowater
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOWATER 95 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer. Ideal for environments with high humidity, also in contact with water. The 14W wheel can be assembled with all medium, heavy and extra heavy-duty castors, including twin wheel versions.

Product line: Polyurethane

EAN13: 8018793255516

EAN5: 25551

Article code: 0901400250LCW



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 1400 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	250
Band width (mm)	60
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	1400
Colour	Blue
Material	Avowater Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/