

SERIE 18AW

18AW

AVO - Wheel with avowater polyurethane for industry, diameter 80mm ean 19499

Material: Avowater Polyurethane

Core: Aluminum

Application field: Industry

Description:

Wheel with aluminium centre coated with polyurethane AVOWATER 91 Shore A for environments with a high amount of humidity and in contact with water. Hub on shielded ball bearings assembled with central spacer. The 18AW wheel can be assembled with all medium and heavy-duty castors.

Product line: Polyurethane

EAN13:8018793194990 **EAN5:**19499 **Article code:**09018A0080LCW



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 180 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	12
Bearing seat (mm)	32X10
Dynamic load capacity (DaN)	180
Colour	Blue
Material	Avowater Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/