

SERIE 14W

# 14W

**AVO - Wheel with avowater polyurethane for industry, diameter 98mm ean 22246**

**Material:** Avowater Polyurethane

**Core:** Cast Iron

**Application field:** Industry

**Description:**

Wheel coated with cast Polyurethane tread AVOWATER 95 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer. Ideal for environments with high humidity, also in contact with water. The 14W wheel can be assembled with all medium, heavy and extra heavy-duty castors, including twin wheel versions.

**Product line:** Polyurethane

**EAN13:**8018793222464

**EAN5:**22246

**Article code:**0901400098LCW



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 275 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 91

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

Diameter (mm)	98
Band width (mm)	30
Hub width (mm)	30
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	275
Colour	Blue
Material	Avowater Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/