

SERIE 17G-CD

17G-CD

AVO - Wheels with polyurethane conductive for industry, diameter 100mm ean 27033

Material: / **Core:** Conductive polyamide 6 **Scope:** Industry

Description:

Wheel coated with conductive (R 10.000 Ohm) injection Polyurethane thread 97 Shore A and conductive polyamide 6 centre. Hub on roller bearings, plain bore or shielded ball bearings assembled with central spacer.

Product line: Antistatic/Conductive

EAN13:8018793270335 **EAN5:**27033 **Article code:**12X17CD100NCG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 120 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	30
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	120
Colour	Grey
Material	/
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/