

SERIE 17CD

17CD

AVO - Wheel with conductive polyurethane for industry, diameter 125mm ean 19212

Material: Conductive Polyurethane

Core: Conductive polyamide 6

Application field: Industry

Description:

Wheel coated with conductive injection polyurethane thread 97 Shore A with conductive polyamide 6 centre. Hub on roller bearings, plain bore or shielded ball bearings assembled with central spacer. The 17CD wheel can be combined with all medium and heavy duty castors.

Product line: Antistatic/Conductive

EAN13:8018793192125

EAN5:19212

Article code:12017CD125NCA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 160 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	35
Hub width (mm)	30
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	160
Colour	Black
Material	Conductive Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/